

MecALAC

SITE DUMPER



MecALAC



SETTING THE STANDARDS IN SITE DUMPER INNOVATION

HAZARD DETECTION CAPABILITY TO FURTHER IMPROVE ON-SITE SAFETY

STOP/START CONTROL FOR IMPROVED FUEL EFFICIENCY AND INCREASED SERVICE INTERVALS

RENTAL TOUGH SKIP DESIGN AND CHASSIS FABRICATIONS FOR UNRIVALLED RELIABILITY

FORWARD AND SWIVEL TIPPING MECHANISMS TO SUIT EVERY APPLICATION

MARKET-LEADING GROUND CLEARANCE FOR SUPERIOR OFF-ROAD PERFORMANCE



AUTOSHIFT TECHNOLOGY FOR INCREASED PERFORMANCE

FOLDING ROPS FOR EASE OF TRANSPORTATION

LARGE OPENING SERVICE DOORS FOR BEST IN CLASS SERVICE ACCESS

HIGH-PERFORMANCE, WATER-COOLED DIESEL ENGINES FOR EFFICIENT OPERATION

CAPTURE TELEMATICS SYSTEM FOR PRECISE FLEET INSIGHT

HIGH-PERFORMANCE DISC BRAKES FOR REDUCED STOPPING DISTANCES



INNOVATION AS STANDARD

Robust, reliable and rental tough, Mecalac site dumpers have been developed using more than 60 years' design and manufacturing expertise.

Featuring state-of-the-art engine technology to meet the latest emissions compliance, each model delivers power, torque and exceptional performance for greater operator productivity and profitability.

Designed with the user in mind, Mecalac site dumpers boast class-leading skip strengths, heavy-duty chassis designs and user-friendly controls. It's easy to see why each model leads its class in on-site earthmoving and tipping.

First-to-market technology additions – including Autoshift transmission, Stop/Start Control, Hazard Detection and Capture telematics – complete the package. From one to ten-tonne payloads, Mecalac's extensive model line-up has the perfect unit for every application.

CONTACT US

Website: www.mecalac.com/construction

Email: construction@mecalac.com

F: /MecalacConstruction

T: @MecalacConstruction





ROBUST AND RELIABLE

POWER TIP SITE DUMPERS

Mecalac Power Tip site dumpers are designed to move material quickly and effectively. From one to ten-tonne payloads, each unit delivers outstanding power and performance.

Featuring state-of-the-art operator technologies, including Start/Stop Control, Autoshift, Capture and Hazard Detection, Power Tip site dumpers set the standards for equipment innovation and performance.

All models are equipped with Tier 4-Final engines, ensuring they meet the highest global emissions standards without the need for exhaust after-treatment.

SPEED AND POWER

With an industry-leading skip wall thickness, heavy-duty steel plates and rental-tough tipping mechanisms, Mecalac site dumpers are designed with reliability in mind. Clever design and the latest technologies ensure smooth and accurate material placement.

Key model benefits:

- Efficient operation
- Improved performance
- Simple operation
- Unrivalled reliability
- Longer service intervals
- Outstanding fuel economy





CREATIVE THINKING

POWER SWIVEL SITE DUMPERS

Mecalac Power Swivel site dumpers are the ideal solution for more challenging jobs. Allowing the load to be rotated before being tipped, Power Swivel technology allows the operator to work within a confined site area.

With payload options ranging between two to six-tonnes, there's a perfect Power Swivel model for every application. High quality slew ring bearings deliver smooth and effective operation – ensuring precise placement of loads.

Featuring state-of-the-art operator technologies, including Start/Stop Control, Autoshift, Capture and Hazard Detection, Power Swivel site dumpers set the standards for equipment innovation and performance.

All models are equipped with Tier 4-Final engines, ensuring they meet the highest global emissions standards without the need for exhaust after-treatment.

MEETING OUTSTANDING SAFETY STANDARDS

All Power Swivel site dumpers feature a heavy-duty locking device, which keeps the skip facing forward while on the move – just one of the many features that ensure each model meets the highest level of on-site health and safety compliance.

Intelligent design means hose routings and hydraulics are protected from damage, without compromising on routine maintenance access.

Key model benefits:

- Efficient operation
- Improved performance
- Simple operation
- Unrivalled reliability
- Longer service intervals
- Outstanding fuel economy



MARKET-LEADING SOLUTIONS

HIGH DISCHARGE SITE DUMPERS

Mecalac High Discharge site dumpers are designed to deliver superior versatility and performance when tipping over obstacles and into skips.

From 1,000-2,000kg payloads, each model has been developed for use in smaller sites – such as housing developments and landscaping projects. All models deliver an impressive height clearance of over 1.5 metres, providing impressive results in confined spaces.

A robust chassis and skip design ensures that the unit remains well balanced and secure while tipping, assuring safe and effective operation.

OUTSTANDING ACCESSABILITY

All Mecalac High Discharge site dumpers feature a folding ROPS to enable easy access into tight spaces. The smallest model in the range, the TA1EH, is capable of passing through a standard one-metre-wide doorway when fitted with optional narrow-width wheels and tyres.

With optional 'narrow-width' designs available for each model in the range, users can specify a customised unit to further increase on-site access and manoeuvrability, as well as increase their range of transportation options.

What this means for you:

- Superior performance
- Suitability for every scenario
- Efficient operation
- Improved performance
- Simple operation
- Unrivalled reliability
- Longer service intervals
- Outstanding fuel economy



LEADING THE WAY IN EQUIPMENT CAPABILITY

MAKING MAINTENANCE EASY

Alongside boasting state-of-the-art product design and first-to-market technology innovation, all Mecalac site dumpers feature superb service access from ground level to ensure simple and time-efficient routine equipment maintenance.

The chassis and engine canopies are designed to give maximum access to all service areas, while engine panels are mounted on heavy-duty, lockable hinges for added safety benefits.

MEETING OUTSTANDING SAFETY STANDARDS



On models with payloads from six-tonnes upwards, Mecalac site dumpers feature a suite of state-of-the-art technologies to deliver outstanding results.

Stop/Start Control has been designed to improve on-site safety, minimise fuel consumption and increase service intervals. The new system will automatically start and stop the engine in predetermined conditions. Tested duty cycles have shown hundreds of pounds of fuel savings per year, as well as extending service intervals by 24 weeks (on a typical 500-hour maintenance schedule).

Developed in-house by Mecalac's engineering department, **Autoshift** uses torque demand to guide gear changes. In challenging and demanding conditions – such as steep gradients and high payloads – Autoshift enables the transmission to hold lower gears for longer, providing torque, power and drive when it's needed most.

Bringing award-winning automotive technology to the construction site, Mecalac's **Hazard Detection** solution uses a microwave radar to provide flawless obstacle detection.

Capture is Mecalac's innovative telematics solution, allowing hire firms and site managers to monitor unit location, distance travelled and hours completed each day. Integration with the ECU offers access to real-time fuel consumption data logs, service planning functionality and geo-fencing reporting to within three metres.







TECHNICAL SPECIFICATIONS



Model	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	*NEW* TA9P	*NEW* TA9S	*NEW* TA9SP	*NEW* TA10P
Payload kg (lbs)	1000 (2205)	2000 (4410)	2000 (4410)	2000 (4409)	3000 (6614)	3000 (6614)	3000 (6614)	3000 (7716)	3500 (6614)	6000 (13228)	6000 (13228)	9000 (19842)	9000 (19842)	9000 (19842)	9000 (19842)	10000 (22046)
Power kW (hp)	15.5 (21)	24.5 (32.6)	24.5 (32.6)	24.5 (32.6)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	55 (74)						
Heaped Capacity litres	540	1200	1200	1200	1950	1880	1950	1880	1880	3780	3530	4587	4587	4150	4150	5046

SITE DUMPER

→ TECHNICAL DATA

PERFORMANCE	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Payload kg (lbs)	1000 (2205)	2000 (4410)	2000 (4410)	2000 (4409)	3000 (6610)	3000 (6614)	3000 (6614)	3000 (6614)	3500 (7716)	6000 (13228)	6000 (13228)	9000 (19842)	9000 (19842)	10000 (22046)
Unladen Weight kg (lbs)	1340 (2954)	1980 (4365)	2120 (4674)	2320 (5115)	2300 (5071)	2360 (5202)	2320 (5115)	2380 (5247)	2380 (5247)	4340 (9568)	4500 (9921)	4920 (10848)	5260 (11596)	5060 (11155)
Tipping Type	Forward Tip – High Discharge	Forward Tip	Swivel Tip	Swivel Tip – High Discharge	Forward Tip	Swivel Tip	Forward Tip	Swivel Tip	Swivel Tip	Forward Tip	Swivel Tip	Forward Tip	Swivel Tip	Forward Tip
Skip Capacity – Water litres	320	750	750	750	1250	1000	1250	1000	1000	1950	1600	2064	1910	2446
Skip Capacity – Struck litres	450	1000	1000	1000	1600	1520	1600	1520	1520	2750	2440	3899	3340	4128
Skip Capacity – Heaped litres	540	1200	1200	1200	1950	1880	1950	1880	1880	3780	3200	4587	4150	5046

ENGINE	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Engine	Kubota D905	Kubota D1703M	Kubota D1703M	Kubota D1703M	Kubota V2203M	JCB EcoMax	JCB EcoMax	JCB EcoMax	JCB EcoMax	JCB EcoMax				
Number of Cylinders	3	3	3	3	4	4	4	4	4	4	4	4	4	4
Gross Power – kW (hp)	15.5 (21)	24.5 (32.6)	24.5 (32.6)	24.5 (32.6)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	32.4 (43.4)	55 (74)	55 (74)	55 (74)	55 (74)	55 (74)
Displacement cc (in³)	898 (54.8)	1647 (100.5)	1647 (100.5)	1647 (100.5)	2197 (134)	2197 (134)	2197 (134)	2197 (134)	2197 (134)	4400 (268.5)	4400 (268.5)	4400 (268.5)	4400 (268.5)	4400 (268.5)
Maximum Torque Nm (lbf.ft)	56 (41)	105 (77.4)	105 (77.4)	105 (77.4)	147 (108.4)	147 (108.4)	147 (108.4)	147 (108.4)	147 (108.4)	400 (295)	400 (295)	400 (295)	400 (295)	400 (295)
Aspiration	Naturally Aspirated									Turbocharged				
Emission Compliance	EU Stage 3A (Tier 3)									EU Stage IIIB / Tier 4 Final				

TRANSMISSION/DRIVE	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Transmission Type	Hydrostatic Pump (Poclair Twinlock) to 4 Hydraulic Wheel Motors	Hydrostatic Motor via Transfer Box to Front & Rear Axles			Manual – 3 Forward / 1 Reverse		Hydrostatic Motor via Transfer Box to Front & Rear Axles			Powershuttle via Transfer Box to Front & Rear Axles		Powershuttle via Transfer Box to Front & Rear Axles – Powershift as option		Powershift via Transfer Box to Front & Rear Axles
Tyre Size	255 / 75 x 15.2 x 8 ply (option 7 x 12 narrow tyre)	10 / 75 x 15.3 (10 ply)			295/80 x 15.3 x 10 ply		295/80 x 15.3 x 10 ply			405–70–20 14PR		500–60–22.5 16PR		
Drive	Hydrostatic 1/1	2 / 2 (High & Low Range – Forward & Reverse) Hydrostatic – Permanent 4WD			3 / 1 Forward and Reverse – Permanent 4WD		2 / 2 (High & Low Range – Forward & Reverse) Hydrostatic – Permanent 4WD			4 / 4 Forward and Reverse – Permanent 4WD				
Maximum Travel Speed – mph (kph)	7 (11)	10 (16)	10 (16)	10 (16)	11.8 (19)	11.8 (19)	11.8 (19)	11.8 (19)	11.8 (19)	16.3 (26.2)	16.3 (26.2)	15.4 (24.8)	15.4 (24.8)	15.4 (24.8)
Gradeability (Maximum Slope Gradient)	20% (1 in 5)	19.5% (1 in 5)	19.5% (1 in 5)	19.5% (1 in 5)	25% (1 in 4)	25% (1 in 4)	25% (1 in 4)	25% (1 in 4)	25% (1 in 4)	25% (1 in 4)	25% (1 in 4)	20% (1 in 5)	20% (1 in 5)	20% (1 in 5)

CAPACITIES	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Fuel Tank Capacity (litres)	35	23	23	23	37	37	37	37	37	65	65	65	65	65
Hydraulic Tank Capacity (litres)	25	25	25	25	37	37	37	37	37	50	50	50	50	–

Note: Metric measurements are the critical values
Dimensions are taken from T152021
- 1 litre = 0.26417 Us liquid gallons
- 1 litre = 0.21997 Imperial liquid gallons

→ TECHNICAL DATA

ENVIRONMENTAL	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Noise Emission (to ISO 4871) – Sound Pressure (LpAd)	83 dB	86.1 dB	86.1 dB	86.1 dB	84 dB	84 dB	84 dB	84 dB	84 dB	81 dB				
Sound Power Level (LWA _d)	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB	101 dB
Noise Compliance	Noise – Equipment Used Outdoors Directive 2000/14/EC													
Vibration – Hand Arm (as defined in EN474-1 all operations)	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²	<2.5 m/s ²
Vibration – Whole Body (as defined in ISO/TR 25398 – Work Cycle)	0.529 rms (0.264 m/s ² Uncertainty)													
HYDRAULIC SYSTEM	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Pump Type	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear	Gear
Flow Rate l/min	29	21	21	21	30	30	30	30	30	60	60	60	60	60
Operating Pressure bar (PSI)	152 (2204)	210 (3050)	210 (3050)	210 (3045.7)	210 (3045.7)	210 (3045.7)	210 (3045.7)	210 (3045.7)	210 (3045.7)	172 (2494.6)	172 (2494.6)	210 (3045.7)	210 (3045.7)	210 (3045.7)
Steering System	Orbitrol hydrostaticsteering unit powering central hydraulic steering ram													

Note: Metric measurements are the critical values
 Dimensions are taken from t152021
 - 1 litre = 0.26417 Us liquid gallons
 - 1 litre = 0.21997 Imperial liquid gallons

BRAKING SYSTEM	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Working Brake	Hydrostatic Dynamic Braking on Rear Wheel Motors	Multi-Plate In-Board Oil Immersed Discs on Front Axle								Foot Brake – Oil immersed discs on front/rear				
Parking Brake	Hydrostatic Dynamic Braking on Rear Wheel Motors	Over Centre Handbrake – Oil Immersed Discs on Front Axle								Over Centre parking brake – Dry disc in gearbox				

ELECTRICAL SYSTEM	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Voltage	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V	12V
Battery	74Ah	74Ah	74Ah	74Ah	74Ah	74Ah	74Ah	74Ah	74Ah	100Ah	100Ah	100Ah	100Ah	100Ah
Alternator	30A	55A	55A	55A	55A	55A	55A	55A	55A	95A	95A	95A	95A	95A

DIMENSIONS		TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S	TA3H	TA3SH	TA3.5SH	TA6	TA6S	TA9	TA9S	TA10P
Total Length	mm (ft in)	2980 (9' 9")	3550 (11' 8")	3570 (11' 9")	3550 (11' 8")	3734 (12' 3")	3952 (13')	3734 (12' 3")	3952 (13')	3952 (13')	4405 (14' 5")	4539 (14' 11")	4484 (18' 9")	4666 (15' 4")	4530 (14' 10")
Total Width	mm (ft in)	984 (3' 3")* / 1110 (3' 8")	1473 (4' 10")	1473 (4' 10")	1473 (4' 10")	1957 (6' 5")	1846 (6' 1")	1957 (6' 5")	1846 (6' 1")	1846 (6' 1")	2300 (7' 7")	2207 (7' 3")	2500 (8' 3")	2380 (7' 10")	2550 (8' 4")
Wheelbase	mm (ft in)	1440 (4' 9")	1900 (6' 3")	1900 (6' 3")	1900 (6' 3")	1939 (6' 4")	1939 (6' 4")	1939 (6' 4")	1939 (6' 4")	1939 (6' 4")	2450 (8' 1")	2450 (8' 1")	2450 (8' 1")	2450 (8' 1")	2450 (8' 1")
Ground Clearance	mm (ft in)	207 (8")* / 284 (11")	184 (7")	184 (7")	184 (7")	279 (11")	279 (11")	279 (11")	279 (11")	279 (11")	385 (1' 3")	385 (1' 3")	374 (1' 3")	374 (1' 3")	374 (1' 3")
Height to Front Lip of Skip (Untipped)	mm (ft in)	1620 (5' 4") (Raised)	1055 (3' 6") (Lowered) / 1644 (5' 5") (Raised)	916 (3')	983 (3' 3")	263 (10")	853 (2' 10")	263 (10")	853 (2' 10")	853 (2' 10")	504 (1' 8")	1258 (4' 3")	490 (1' 7")	1215 (4')	490 (1' 7")
Turning Radius to Outside of Skip	mm (ft in)	2326 (7' 8")	3610 (11' 10")	3610 (11' 10")	3610 (11' 10")	4711 (15' 6")	4553 (14' 11")	4711 (15' 6")	4553 (14' 11")	4553 (14' 11")	5863 (19' 3")	5726 (18' 10")	5994 (19' 8")	5816 (19' 1")	6011 (19' 9")
Steering Angle		+/- 45°	+/- 30.6°	+/- 30.6°	+/- 30.6°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°	+/- 30°
Oscillation		+/- 14°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10.5°	+/- 10°	+/- 10°	+/- 10°	+/- 10°	+/- 10°
Height to Top of ROPS (Raised with beacon)	mm (ft in)	2837 (9' 4")	2940 (9' 8")	2940 (9' 8")	2940 (9' 8")	2920 (9' 7")	2920 (9' 7")	2920 (9' 7")	2920 (9' 7")	2920 (9' 7")	3306 (10' 10")	3306 (10' 10")	3668 (12' 1")	3668 (12' 1")	3668 (12' 1")

→ STANDARD AND OPTIONAL EQUIPMENT

TA1EH STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock
Wide Tyres (255 / 75 x 15.2 8ply)

TA1EH OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors
CESAR Datatag Security
Spare Wheel
Special Paint
Narrow Tyres (7 x 12)
High Visibility Safety Decals for Steps & Handrails
German / Swiss Road Homologtation Kit

TA2H TA2SH TA2SEH STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Leg Guard
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock

TA2H TA2SH TA2SEH OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors (standard in some markets - check with your local Mecalac dealer)
CESAR Datatag Security
Fan Guard (standard in some markets - check with your local Mecalac dealer)
Spare Wheel
Special Paint (standard in some markets - check with your local Mecalac dealer)
High Visibility Safety Decals for Steps & Handrails
German / Swiss Road Homologtation Kit

TA3 TA3S STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Leg Guard
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock

TA3 TA3S OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors (standard in some markets - check with your local Mecalac dealer)
CESAR Datatag Security
Fan Guard (standard in some markets - check with your local Mecalac dealer)
Spare Wheel
Special Paint (standard in some markets - check with your local Mecalac dealer)
High Visibility Safety Decals for Steps & Handrails

TA3H TA3SH TA3.5SH STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Leg Guard
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock

TA3H TA3SH TA3.5SH OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors (standard in some markets - check with your local Mecalac dealer)
CESAR Datatag Security
Fan Guard (standard in some markets - check with your local Mecalac dealer)
Spare Wheel
Special Paint (standard in some markets - check with your local Mecalac dealer)
High Visibility Safety Decals for Steps & Handrails
German / Swiss Road Homologtation Kit

TA6 TA6S STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock
Water in Fuel Monitoring

TA6 TAS OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors (standard in some markets - check with your local Mecalac dealer)
CESAR Datatag Security
Fan Guard
Spare Wheel
Special Paint
High Visibility Safety Decals for Steps & Handrails
German / Swiss Road Homologation Kit
Biodegradable Hydraulic Oil
Leg Guard

TA9 STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock
Wide Tyres (255 / 75 x 15.2 8ply)
Water in Fuel Monitoring
Coolant Level Monitoring

TA9 OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors
CESAR Datatag Security
Fan Guard
Spare Wheel
Special Paint
Narrow Tyres (7 x 12)
High Visibility Safety Decals for Steps & Handrails
Biodegradable Hydraulic Oil
Leg Guard

TA9S STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock
Water in Fuel Monitoring

TA9S OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors (standard in some markets - check with your local Mecalac dealer)
CESAR Datatag Security
Fan Guard
Spare Wheel
Special Paint
High Visibility Safety Decals for Steps & Handrails
Biodegradable Hydraulic Oil
Leg Guard

TA10P STANDARD

Folding ROPS Frame
Reversing Alarm
Flashing Beacon
Towing/Recovery Bracket
Hour Metre
Seat Belt (High Visibility Orange)
Seat (adjustable fore/aft, operator weight and back angle)
Heavy Duty Articulation Lock
Wide Tyres (255 / 75 x 15.2 8ply)
Water in Fuel Monitoring
Coolant Level Monitoring

TA10P OPTIONS

LED Flashing Beacon
Road Lights (RTA) including Front Light Guards
L/H & R/H Rear View Mirrors
CESAR Datatag Security
Fan Guard
Spare Wheel
Special Paint
Narrow Tyres (7 x 12)
High Visibility Safety Decals for Steps & Handrails
Biodegradable Hydraulic Oil
Leg Guard



Mecalac

#mecalac

Mecalac