

Impact Wrenches

Construction,
Industrial & Automotive



MI-17HEG

INDUSTRIAL


- 650Nm Maximum torque output
- 1/2" Square drive
- Suitable for industrial & vehicle maintenance applications
- Compact & lightweight
- Twin hammer impact mechanism
- 4 Level power adjustment
- Exhausts through rubber sealed grip with integrated silencer for increased operator comfort
- Steel hammer case for increased durability
- Vibration level 7.4m/s²

Type	MI-17HEG
Brand	TOKU
Square drive	1/2"
Type	Ring type
Bolt capacity mm	16
Impact mechanism	Twin-Hammer
RPM	5,500
Torque Nm	650
Power adjustment	R/L 4 levels
Air cons. l/s	8.3
Weight kg	2.4
Inlet thread	PT 1/4"
Hose diameter mm	10
Vibration m/s ²	7.4
Noise level dB(A)	88




TECHNICAL DATA

Type	A mm	A* mm	B mm
MI-17HEG	178		31



IMPACT MECHANISMS



The twin-hammer system makes 2 impacts per rotation at both sides of the anvil. Same principal as the 2-hammer system, manufactured differently.

ELV - Daily Exposure Limit Value
EAV - Daily Exposure Action Value

Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
MI-17HEG	3.39	0.55



REPAIR & SERVICE DEPARTMENT

From the Yokota UK service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service