

SE4000DLES

4.0kVA Silent Diesel Generator

GENERATOR SPECIFICATION

Voltage	230/115
Phase	1
Frequency	50Hz
Prime Power (PRP)	4.0kVA / 3.2kW
Alternator	NSM K100F
Alternator Type	Brushless - Smooth Waveform
Fuel tank capacity	13.0 Litres
Autonomy 75% load	13.0 Hours
LWA	97
dBA @ 7M	71

ENGINE SPECIFICATION

Engine	Kohler KD15-350GE530
Emissions certified	Stage V
Cylinders	Single
Distribution	O.H.V.
Aspiration	Normally aspirated
Cooling	Air
Displacement	349 cm ³
Rpm	3000
Starting system	Key - Electric start
Fuel	Diesel



KOHLER
IN POWER. SINCE 1920.

DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	
775	475	560	92



CONTROL BOX

- 1 x 16A & 1 x 32A 115V BS4343 sockets.
- 1 x 16A 230V BS4343 socket.
- Reset circuit breaker overload protection.

STANDARD FEATURES

- Key start.
- Low oil pressure & battery charge fail warning lamps.
- Long run fuel tank.
- Easy carry fold-away handles.
- Brushless smooth waveform alternator.

OPTIONS

- Single voltage.
- Trolley kit.

POWER DEFINITION

Prime Power (PRP) : Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.