









PREMIER XT SITE CEMENT MIXERS







FEATURES & BENEFITS

- Extra heavy-duty and robust chassis designed to withstand the worst site conditions.
- Extra rigid and reinforced drum to prevent distortion.
- Heavy duty wheels designed to operate in the toughest of conditions.
- Stage 5 compliant Yanmar L48 Electric-Start Diesel engine.
- Foot operated tip-lock and large tip wheel for added safety and control with large mixes.
- Enhanced mixing performance with 'Quick Mix' replaceable bolt in paddles.
- Easy-to-clean tubular chassis.
- New wider profile wheels for extra stability.
- Sealed, heavy-duty high specification gearbox reduced maintenance.
- Lockable stay cool engine compartment for security and lid down operation.
- Extra short wheel base on 100XT and 150XT to fit on compact vehicle tail lifts.



'QUICK MIX' BOLT-IN PADDLES



NEW WIDER PROFILE WHEELS FOR EXTRA STABILITY

TECHNICAL SPECIFICATIONS

Model

Dimensions (wxLxh) Max Drum Volume Max Mixing Capacity Drum Speed

Model

Model Code Engine Power Weight

Model

Model Code Engine Power Weight

Model

Dimensions (wxLxh) Max Drum Volume Max Mixing Capacity Drum Speed

Model

Model Code Engine Power Weight

Model

Model Code Engine Power Weight

Premier 100XT

(mm) 900x1475x1765 (ltr) 250 (ltr) 110 (rpm) 19

100XT Yanmar E/S

PM20V (Hp / kW) 3 / 2.5 (kg) 335

100XT Electric

PM08 - 110v, PM06 - 230v (Hp/kW) 2 / 1.5 (kg) 303.5

Premier 150XT

(mm) 900x1560x1765 (ltr) 300 (ltr) 160 (rpm) 19

150XT Yanmar E/S

PM38V (Hp / kW) 3.4 / 2.5 (kg) 344

150XT Electric

PM28 - 110v, PM45 - 230v (Hp/kW) 2 / 1.5 (kg) 312.5

Model

Dimensions (wxLxh) Max Drum Volume Max Mixing Capacity Drum Speed

Model

Model Code Engine Power Weight

Model

Model Code Engine Power Weight

Model

Dimensions (wxLxh) Max Drum Volume Max Mixing Capacity Drum Speed

Model

Model Code Engine Power Weight

Model

Model Code Engine Power Weight

Premier 175XT

(mm) 900x1520x1890 (ltr) 350 (ltr) 180 (rpm) 19

175XT Yanmar E/S

PM39V

(Hp / kW) 3.4 / 2.5 (kg) 350

175XT Electric

PM31 - 110v, PM46 - 230v (Hp/kW) 2 / 1.5 (kg) 322.5

Premier 200XT

(mm) 900x1590x1890 (ltr) 400 (ltr) 220 (rpm) 19

200XT Yanmar E/S

PM40V (Hp / kW) 3.4 / 2.5 (kg) 353.5

200XT Electric

PM42 - 110v, PM47 - 230v (Hp/kW) 2 / 1.5 (kg) 323



ALTRAD BELLE

Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB

Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com

www.Altrad-Belle.com www.ALTRAD-Belle247.com

