

SULLAIR NEEDLE SCALERS

Applications

The Sullair SANS needle scaler removes rust, scale, paint and weld splatter from irregular surfaces; and converts easily to a weld flux scaler. This versatile tool features an adjustable needle exposure and 19 steel needles (round pattern) as standard. Optional beryllium copper (non-sparking) needles are available.

Built-in durability

Sullair scalers are constructed of advanced materials for lighter weight and greater durability inside and out. Smooth, black oxide exterior allows easy clean-off of debris.

Lubrication

Due to the design tolerances of these tools, an in-line oiler should be used during operation.

90-day parts warranty

The Sullair warranty covers all scaler parts against manufacturing defects.

Front exhaust

This feature provides cleaner working conditions.

SULLAIR SCALER SPECIFICATIONS

	SANS	SCWF
Net Weight	6½ lbs.	4 lbs.
Length	17½"	9½"
Shipping Weight	8 lbs.	6 lbs.
Bore and Stroke	1" X 1⅛"	1" X 1⅛"
Blows/min.	4600	4600
Air Consumption	14 cfm	14 cfm
Air Inlet	⅜" FNPT	⅜" FNPT



Accessories include line oiler, hose and steels made specifically for Sullair needle scalers and weld flux scalers.

SULLAIR CONCRETE VIBRATORS

Applications

Concrete Vibrators are designed for low slump pours of concrete footings, slabs and walls. The correct diameter tool depends on wall thickness or concrete depth.

- Plated cylinders, easy to clean.
- Adjustable throttle for optimum performance.
- Only one moving part.
- Minimum on site lubrication.
- Standard hose length 10'.



SULLAIR CONCRETE VIBRATOR SPECIFICATIONS

	MCV-300	MCV-400	MCV-580	MCV-780
Diameter	1⅜"	1½"	2¼"	3⅛"
Weight	5.3 lbs.	9 lbs.	18 lbs.	33 lbs.
Air Required	16 cfm @ 90 psi	17 cfm @ 90 psi	35 cfm @ 90 psi	51 cfm @ 90 psi
Hertz	18000	17000	16000	13000