









COMMODORE SITE CEMENT MIXERS







FEATURES & BENEFITS

- Extra heavy-duty and robust chassis designed to withstand the worst site conditions.
- Rigid and reinforced drum to prevent distortion.
- Foot operated tip-lock and large tip wheel for added safety and control with large mixes.
- Stage 5 compliant Yanmar L48 Electric-Start Diesel engine.
- High quality mixing performance from gated paddle design.
- Easy-to-clean tubular chassis.
- New wider profile wheels for extra stability.
- Sealed, heavy-duty high specification gearbox reduced maintenance.
- Robust, easy to use Parking Brake for increased on-site safety.
- 3 Drum sizes available to suit all your site needs.



'QUICK MIX' BOLT-IN PADDLES



NEW WIDER PROFILE WHEELS FOR EXTRA STABILITY

TECHNICAL SPECIFICATIONS

Model		Commodore 5 - 3	Commodore 7 - 5	Commodore 10-7
Part No.		COM53VYEY	COM75VYEY	COM107VYEY
Overall Width	(mm)	900	900	900
Overall Height	(mm)	1300	1415	1430
Overall Length	(mm)	1900	1900	1850
Loading Height	(mm)	1060	1140	1200
Discharge Height	(mm)	720	620	580
Wheel Diameter	(mm)	350	350	350
Overall Height (Door Open)	(mm)	1710	1710	1710
Wheel Base	(mm)	1140	1140	1400
Engine Power	(Hp/kW)	3/2.5	3/2.5	3/2.5
Cubic Feet In / Out		5/3	7/5	10/7
Mixed Batch Output	(ltr)	110	160	220
Max Drum Capacity	(ltr)	250	300	400
Max Mixing Capacity	(ltr)	160	220	310
Drum Speed	(rpm)	19	19	19
Weight	(kg)	418	423	438



