



1501

Wheel dumper

The multi-talent in mini-format

The twin-lock 4-wheel drive system makes the 1501 a perfect partner for uneven or steep terrain. The articulated pendulum joint adapts to all uneven terrain providing the necessary stability. The high tip skip, equipped as standard, as well as the optionally available swivel tip skip, ensure that no requirements for use are overlooked. A fold-down roll over protection system and the small dimensions make it convenient to transport. The optional reverse alarm, rotating beacon and outside review mirrors enhance safety. Wide leg protection, the fold-down roll-over protection system and the large control station provide safer and intuitive operation.

Highlights

- Swivel tip skip

Technical Data

Hydraulic

hydraulikpump	ZRP
flow rate	25,0 l/min

Mechanical - Output Details

Gradeability	50,0 %
Travel speed	16,0 km/h

Mechanical Details

Length	3.300,0 mm
Width	1.305,0 mm
Height	2.550,0 mm
Weight	1.320,00 kg
Dry Weight	1.336,0 kg
gross vehicular weight	2.836,0 kg
Payload	1.500,0 kg
skip capacity levelled	650,0 l
Skip capacity heaped	800,0 l
Pendulum angle	15,0 °
Axle load Front	2.000,0 kg
Axle load Rear	1.100,0 kg

Aggr. pwr time limited 1~(LTP)	1.336,0 kg
--------------------------------	------------

Engine

Engine type	Diesel engine
Cylinder capacity	1.116,0 cm3
tank capacity	15,0 l
Effective power	17,0 KW
Nominal Engine speed	3.000,0 1/min
Standard (Effective power)	ISO 3046
Manufacturer	Yanmar
Engine designation	3TNV76

Environment Data

Sound power LWA, guaranteed	101,0 dB(A)
-----------------------------	-------------

Chassis

turning radius	3.300,0 mm
articulation angle	33,0 °
hydraulikpump	axialpistonpump
flow rate	135,0 l/min

Shipping and Storage

Shipping weight	1.186,0 kg
-----------------	------------

Dimensions

A1	Height ROPS	2,550 mm
A4	Height of ROPS tilted	1,960 mm
B3	Width of vehicle	1,350 mm
B4	Width of skip	1,225 mm
D1	Wheel base	1,650 mm
E1	Rear overhang	810 mm
F1	Dumping width	400 mm
G1	Dumping height max.	370 mm
G2	Dumping height max., high tip skip raised	1,450 mm
H1	Skip height	1,345 mm
H3	Skip height tilted, high tip skip raised	2,975 mm
I1	Ground clearance	260 mm