

IF YOUR DEHUMIDIFIER FAILS TO OPERATE

1. Check that the plug is fully pushed into the socket and is switched on.
 2. Check with some other electrical device that the wall socket is "live". If it is not, contact a qualified electrician.
 3. Check the fuse in the plug. If you replace the fuse, refit with a 13Amp fuse.
 4. Check the humidistat control is turned clockwise.
 5. Check that the water container is not full.
- Should none of the above remedies work, then disconnect from the mains. Contact the help line on 01388 664400. DO NOT attempt to repair the unit or unscrew the outer casing.

ELECTRICAL CONNECTION

If the appliance is fitted with a plug for which your socket is unsuitable, then it should be cut off and an appropriate plug fitted.

This appliance complies with the suppression requirements of the EEC direction 82/199/EEC as embodied in BS800:1988.

IMPORTANT:- The wires in this mains lead are coloured in accordance with the following code:-

Green & Yellow	Earth
Blue	Neutral
Brown	Live

As the colours of the wires in the mains lead of this appliance may not correspond with the coloured markings identifying the terminals in your own plug, proceed as follows:

The wire which is coloured Green and Yellow must be connected to the terminal in the plug which is marked with the letter E or by the Earth Symbol or coloured Green and Yellow. The wire which is coloured Blue must be connected to the terminal in the plug which is marked with the letter N or coloured Black. The wire which is coloured Brown must be connected to the terminal which is marked with the letter L or coloured Red.

You must dispose of the non rewirable plug once it has been removed from the flexible cord. It is dangerous to attempt to insert the plug into any electrical socket elsewhere in the house. If the flexible cord becomes damaged it must be replaced by an identical cord.

CHANGING THE FUSE

Only 13 Amp fuses that are ASTA approved to BS1362 should be used.

The fuse cover must be refitted after replacement of the fuse. In the event of the fuse cover being lost or damaged, the plug must not be used until a replacement is obtained. Replacement fuse covers, which must be coloured BLACK, are obtainable from electrical retailers.

WARNING – THIS APPLIANCE MUST BE EARTHED

TECHNICAL SPECIFICATIONS

CD35	230V/50Hz/1 Phase
Height	550 mm
Width	345 mm
Depth	350 mm
Weight	26 kg
Min Operating Temperature	1 °C
Max Operating Temperature	35 °C
Water Extraction (24hrs) 32°C / 90%RH	10 l
Max Power Consumption 32°C / 90%RH	250 W
Max Running Current	2 A
Fuse Rating (UK)	13 A